

# EXPLORER 300

Portable Inmarsat BGAN terminal

**COBHAM**

2013 Data Sheet

The most important thing we build is trust



# EXPLORER 300

Portable Inmarsat BGAN terminal

## Compact - for individual usage

EXPLORER 300 makes it easy to stay connected anywhere in the world. It is complete broadband connectivity the size of a netbook.

It is ideal for single travelers who frequently change location, consisting of only one unit – a transceiver with an integrated antenna.

## The smallest BGAN terminal

The smallest terminal in the EXPLORER series. Weighs only 1.4 kg. Dimensions: 16.8 x 21.7 x 5.2 cm.

## Single User terminal

The ideal combination of performance and portability. Provides simultaneous high quality voice and broadband access at speeds up to 464 kbps. It supports LAN, USB, Bluetooth and phone/fax interfaces.

# COBHAM

## Compact and lightweight

Ideal if you primarily need voice, or moderate speed standard IP internet access.



## Specifications

### Dimensions

Total H / W / D:	168 / 217 / 52 mm 6.6 / 8.5 / 2.1 inches
------------------	---

**Weight (incl. battery):** 1.4kg / 3.1lbs

### Data capabilities

Standard IP:	Up to 384 kbps
Streaming IP:	32, 64 kbps

### Voice capabilities

Standard voice:	4 kbps
Premium voice:	3.1 kHz audio, 64 kbps

### Text capabilities

SMS:	160 characters
------	----------------

### Inmarsat frequencies:

1525.0 – 1559.0 MHz (Rx)
1626.5 – 1660.5 MHz (Tx)

### EIRP:

10dBW ±1dB
------------

<b>LCD display:</b>	Graphical high resolution, back lit
<b>User interface:</b>	Four navigation keys and powerbutton Audio and LCD pointing aids. LED indicators. Thrane & Thrane web interface
<b>Languages:</b>	UK, FR, DE, ES, RU and CN
<b>Approvals:</b>	CE, FCC, GMPCS Inmarsat Class 3 Type Approval

## Interfaces

### 1 x Analogue RJ-11 phone / fax interface

### 1 x Bluetooth interface (Version 1.2)

Antenna:	Integrated in transceiver unit
Frequencies:	2400.0 – 2483.5 MHz
Max. coverage outdoor:	25m / 82ft
Max. devices connected:	1 handset, 1 PC/PDA
Profiles supported:	Cordless handset, serial port, service discovery application, dial-up networking, headset
Standard:	Power class 2

### 1 x LAN interface

Connector type:	RJ-45, MDI-X
Data rate:	10/100 Mbps
Max. cable length:	100m / 328ft (Cat5 UTP)
Standard:	ISO/IEC 8877:1992, and IEEE 802.3 (1998 edition)

### 1 x BGAN SIM-Card slot

## Environmental conditions

### Temperature

Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F

### Battery storage temperature

1 month:	-20°C / -4°F to +60°C / +140°F
3 months:	-20°C / -4°F to +45°C / +113°F
1 year:	-20°C / -4°F to +20°C / +68°F

### Relative humidity:

95% non-condensing at +40°C / +104°F
---

### Robustness:

0.5 m / 1.64 ft drop on concrete (operational, 95% survival)
---

### Storage temperature:

-40°C to +80°C (ex. battery) -40°F to +176°F (ex. battery)
---

### Water and dust:

IP-54 (dust and spray proof)
------------------------------

## Power

**DC input range:** 10-16VDC

### Power consumption

Standby / transmit:	0.8W / 14W (typical)
During charging:	38W (max.)
Connector type	2.5mm EIAJ RC-5320-IV

### AC/DC power supply

Input:	100-240VAC, 47-63Hz, 50W
Output:	15VDC

### Battery:

Lithium ion (rechargeable)	
Stand-by time:	36h, 0°C/+32°F to 55°C/+131°F
Standard call:	3h, 0°C/+32°F to 55°C/+131°F
Premium voice call:	1h30m, 0°C/+32°F to +55°C/+131°F
Receive time, max.:	3h30m @ 128kbps, (25°C / 77°F)
Transmit time, max.:	2h15m @ 128kbps,
Min. number of charges:	300
Recharge time:	Less than 3 hours
Charge temperature:	0°C / +32°F to +45°C / +113°F

## Other features

Phonebook; Fax; Message indicator; Traffic logging; Admin control (password protected); Webserver; Router or direct mode; Network Management; DHCP; Remote Management; Up to 11 x PDP context; Point-to-point Protocol over Ethernet (PPPoE).

## Package

EXPLORER 300 terminal incl. rechargeable lithium ion battery LAN cable and 100-240VAC power supply.  
Getting started kit - Quick start guide, CD with manuals.

## Product number

403705A-00700 EXPLORER 300 Terminal

For further information please contact:

Cobham SATCOM  
Lundtoftegaardsvej 93 D  
DK-2800 Kgs. Lyngby  
Denmark  
www.cobham.com  
Tel: +45 3955 8800  
Fax: +45 3955 8888

